

NEW



EasyCut B 950 Collect

Mowercombination





EasyCut B 950 Collect

- Butterfly mower combination without conditioners but with merger augers that merge the cut material into one central swath
- Light-weight and compact design
- The swathing modes: Central swathing, independent swathing or no swathing.
Each option is selected from the tractor seat and on the move.
- Hydraulic suspension system
- Impact damage protection



Technical data

9.45 m (31')	work width incl. front mower
3.60 m (11'10")	work width incl. rear mower
3.00 m (9'10")	transport width
4.00 m (13'1.5")	storage height
4.00 m (13'1.5")	transport height (25 cm ground clearance)
12	discs (6 per unit)
4	drums (2 per unit)
Standard	quick-change blades
Standard	SafeCut

Standard	SmartCut
45 cm (1'6")	diameter merger augers
1.50 m (4'11")	gap between the merger augers
1000 rpm	pto speed
Hydraulic system	2da plus load-sensing
2,988 kg (6587 lbs)	weight
145/200 kW/hp	input power
up to 14 ha/h	area output

All specifications, weights and dimensions do not necessarily comply with standard specifications and are therefore not binding.



The merger augers

The high-performance and sturdy merger augers are 45 cm (1'6") in diameter and are mounted closely behind the cutterbars. They feed massive amounts of crops in a consistent flow to the middle forming a uniform swath.

The drive

The merger augers are not driven by belts but by a powerful angular gearbox.



The swathing modes

There are three swathing modes: swathing, independent swathing or no swathing. The mode is selected by opening and closing the decks behind the augers.



The hydraulic suspension

The EasyCut B 950 Collect mowers feature hydraulic suspension which allows operators to adjust contouring from the electric control box in the cab. The level of response is set steplessly and the current setting is read out on a pressure gauge that is easily read from the cab.



The three-point hitch

The DuoGrip system suspends each unit in its center of gravity and provides extra guidance by lateral arms for superior ground contour hugging. The rear lights can be raised hydraulically to clear the way for more material to pass through this area. Lowered into transport position, they give exemplary road safety.



Independent liftout

Operators can raise one mower when cutting wedges. Simply select the mower on the electric control box and lift it out hydraulically.



Maschinenfabrik Bernard Krone

Perfect in every detail



Innovative, proficient and close to our customers – these are the keywords that mark the philosophy of our family-owned company. As a forage specialist, KRONE manufactures disc mowers, tedders, rakes, forage wagons, round and square balers as well as the high-capacity and self-propelled BiG M mower conditioners and our BiG X forage harvesters.

Quality made in Spelle – since 1906.

Your KRONE dealer

 **KRONE**
THE POWER OF GREEN

Maschinenfabrik Bernard KRONE GmbH & Co. KG

Heinrich-Krone-Straße 10
D-48480 Spelle

Phone: +49 (0) 5977 935-0
Fax: +49 (0) 5977 935-339

info.ldm@krone.de | www.krone.de